

for Commercial Suspended Ceilings

Flexible sprinkler hose with threaded end fittings are for use in commercial suspended ceilings. The flexible hoses are to be installed according to the manufacturer's directives. Unless indicated, the hoses have a rated working pressure of 175 psi (1205 kPa).

Models 2024I, 2036I, 2048I, 2060I, 2072I

<i>Model</i>	<i>NPT in.</i>	<i>Hose Assembly length ft (m)</i>	<i>Equivalent Length of 1 in. Schedule 40 Pipe, ft (m)</i>
2024I	1/2	2 (0.6)	3.5 (1.1)
2036I	1/2	3 (0.9)	4.8 (1.5)
2048I	1/2	4 (1.2)	6.8 (2.1)
2060I	1/2	5 (1.5)	8.5 (2.6)
2072I	1/2	6 (1.8)	8.9 (2.7)

The "I" indicates an "Institutional" flexible hose with a pressure rating of 175 psi (1205 kPa). Approval of these models of flexible metal sprinkler hose is limited for use with the following applications:

- Pendent and horizontal sidewall applications with a UH-1 ceiling / wall bracket manufactured by FlexHead Industries Inc. The FlexHead bracket, UH-1 (Universal Hub), is a one piece unit.
- Sidewall application with a Tolco-BR-22 uni-strut type hanger manufactured by FlexHead Industries Inc. The channel length is limited to a 6 and 12 inch.

Company Name:	FlexHead Industries Inc
Company Address:	56 Lowland St, Holliston, Massachusetts 01746, USA
Company Website:	http://www.flexhead.com
Listing Country:	United States of America
Certification Type:	FM Approved