



VENF.EX5269 Flexible Sprinkler Hose with Fittings

[Page Bottom](#)

Flexible Sprinkler Hose with Fittings

See General Information for Flexible Sprinkler Hose with Fittings

FLEXHEAD INDUSTRIES INC

EX5269

LOWLAND IND PARK
56 LOWLAND ST
HOLLISTON, MA 01746 USA

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
2024	175	300	1 by 1/2	2	3	3	11	Limited
2036	175	300	1 by 1/2	3	3	3	16	Limited
2048	175	300	1 by 1/2	4	4	3	24	Limited
2060	175	300	1 by 1/2	5	4	3	29	Limited
2072	175	300	1 by 1/2	6	4	3	35	Limited
2024	175	300	1 by 3/4	2	3	3	12	Limited
2036	175	300	1 by 3/4	3	3	3	18	Limited
2048	175	300	1 by 3/4	4	4	3	23	Limited
2060	175	300	1 by 3/4	5	4	3	29	Limited
2072	175	300	1 by 3/4	6	4	3	32	Limited
2024H	300	300	1 by 1/2	2	3	3	11	Limited
2036H	300	300	1 by 1/2	3	3	3	16	Limited
2048H	300	300	1 by 1/2	4	4	3	24	Limited
2060H	300	300	1 by 1/2	5	4	3	29	Limited
2072H	300	300	1 by 1/2	6	4	3	35	Limited
2024H	300	300	1 by 3/4	2	3	3	12	Limited
2036H	300	300	1 by 3/4	3	3	3	18	Limited
2048H	300	300	1 by 3/4	4	4	3	23	Limited
2060H	300	300	1 by 3/4	5	4	3	29	Limited
2072H	300	300	1 by 3/4	6	4	3	32	Limited
2024E	175	300	1 by 1/2	2	3	3	19	Limited
2036E	175	300	1 by 1/2	3	3	3	23	Limited
2048E	175	300	1 by 1/2	4	4	3	27	Limited
2060E	175	300	1 by 1/2	5	4	3	32	Limited
2072E	175	300	1 by 1/2	6	4	3	35	Limited

2024E	175	300	1 by 3/4	2	3	3	18	Limited
2036E	175	300	1 by 3/4	3	3	3	23	Limited
2048E	175	300	1 by 3/4	4	4	3	23	Limited
2060E	175	300	1 by 3/4	5	4	3	29	Limited
2072E	175	300	1 by 3/4	6	4	3	32	Limited
2024HE	300	300	1 by 1/2	2	3	3	19	Limited
2036HE	300	300	1 by 1/2	3	3	3	23	Limited
2048HE	300	300	1 by 1/2	4	4	3	27	Limited
2060HE	300	300	1 by 1/2	5	4	3	32	Limited
2072HE	300	300	1 by 1/2	6	4	3	35	Limited
2024HE	300	300	1 by 3/4	2	3	3	18	Limited
2036HE	300	300	1 by 3/4	3	3	3	23	Limited
2048HE	300	300	1 by 3/4	4	4	3	23	Limited
2060HE	300	300	1 by 3/4	5	4	3	29	Limited
2072HE	300	300	1 by 3/4	6	4	3	32	Limited

All models of flexible sprinkler hose with fittings are intended to be installed with the MP-24-BKT-2 bracket in accordance with the manufacturer's installation instructions dated June 11, 2009.

The model 2024-2072 and 2024H-2072H flexible sprinkler hoses with fittings are also intended to be installed with the AD-24-BKT-2 and AD-16-BKT-2 brackets in accordance with the manufacturer's installation instructions dated March 20, 2009.

Last Updated on 2009-08-04

[Questions?](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2009 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2009 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

